

SurgeArrest Home/Office

APC Home/Office Surge Protector, 8 outlet, phone line (w/splitter) protection, 120v

P8T3



Professional-grade Protection for Computers and Electronics

Includes: Cord management straps, Telephone Cable, User Manual


Usually in Stock

Technical Specifications

Output

Number of Outlets	8
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz
Input Connections	NEMA 5-15P 
Cord Length	6 feet (1.83 meters)
Input Breaker Capacity	15A

Surge Protection and Filtering

Surge energy rating	1750 Joules
eP Joule Rating	2525
EMI/RFI Noise rejection (100 kHz to 10 MHz)	70 dB
Data Line Protection	RJ-11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines)
Data Lines Protected (multi-line only)	1-4
Let Through Voltage Rating	< 85

Physical

Net Weight	2.02 lbs. (0.92 kg)
------------	---------------------

Maximum Height	1.25 inches (32 mm)
Maximum Width	3.50 inches (89 mm)
Maximum Depth	13.00 inches (330 mm)
Shipping Weight	2.42 lbs. (1.10 kg)
Shipping Height	2.36 inches (60 mm)
Shipping Width	5.59 inches (142 mm)
Shipping Depth	14.17 inches (360 mm)
Master Carton Units	6.00
Master Carton Dimensions (Length x Width x Height)	15 x 8 x 12 inches (392 x 198 x 302 mm)
Master Carton Weight	16.50 lbs. (7.50 kg)
Color	Black

Environmental

Operating Environment	32 - 113 °F (0 - 45 °C)
Operating Relative Humidity	0%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
Storage Relative Humidity	0%
Storage Elevation	0-50000 feet (0-15000 meters)

Conformance

Regulatory Approvals	CSA,NOM,UL 1363,UL 1449
Standard Warranty	Lifetime
Equipment protection policy	Lifetime : \$75000
UL 1449 TVSS Rating	330V

*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.